

UNINTERRUPTIBLE POWER SYSTEM (UPS)

3KVA, 2.6KW Double Conversion On Line Isolated UPS with 115VAC, 60Hz Input, 120VAC, 60Hz Output, Power Factor Correction, Multiple Relay Contact Status Signals and Internal Automatic Bypass for Navy Shipboard Applications.



Part # FA00126

Model # IHT3KRM-M-2.6kw-115v-Isol-120v-3U25LMS

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA00126
IP Model #:	IHT3KRM-M-2.6kw-115v-Isol-120v-3U25LMS
Unit Description:	3KVA, 2.6KW Double Conversion On Line Isolated UPS with 115VAC, 60Hz Input, 120VAC, 60Hz Output, Power Factor Correction, Multiple Relay Contact Status Signals and Internal Automatic Bypass for Navy Shipboard Applications.
SPECIFICATIONS	
Power Rating (VA, Watts):	3000 VA, 2600 W (combines with FA00124 for 5.6kW)
Input AC Voltage (AC Voltage, tolerance):	Mains input P14: 115VAC, (-20% to +20%)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	Mains input P14: 60Hz
Input Max Current (Amps):	Mains input P14: 35 Amps
Output AC Voltage (AC Voltage, tolerance):	1 output J19 at 120 VAC (±3%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	1 output J19 at 60 Hz
Output Sync Requirements:	1 output J19 sync to (±5%)
Enclosure Type & Size (type/rack unit, dimensions):	Rack Mountable 4U, 6.97"H x 17"W x 25"D
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	P14: 1 each mains input
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	J19: 1 each Circular Mil; J16: 1 each circular mil, output to FA00124
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	N/A
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V2.9Ah, Lead Acid
Battery Total Quantity:	8
Battery String Voltage:	96
Battery String (number of strings, quantity per string)	1, 8
Battery Minimum Run Time (approx. run time at #watts):	10 seconds at 2433 W
Battery Mounting (hot swap/fixed):	Hot Swap
Temperature:	0C to 50C Operating; -40C to 70C Storage;
Humidity:	0-95%, Non-Condensing
PFC Feature:	Yes
Isolation (galvanic isolation/non-isolated):	Galvanic Isolation
Application (shipboard/airborne/ground/all):	Shipboard
Fan Filters (EMI/dust/comboination/grill):	Combination dust/EMI on front, EMI on rear
Auto Start (manual start/auto start):	Auto start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	J18: RS-232, DE-9 D-subminiature, Opto-Isolated, Rear Panel
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	J15: Circular Mil; trip, fail, & battleshort comm. with FA00124
Breaker & Switch Input (rating, type, location):	Toggle Switch, Front Panel CB1-2 for P14
Breaker & Switch AC Output (rating, type, location):	Push to Reset, Front Panel for J19
Breaker & Switch DC Output (rating, type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Un-bonded

ISO 9001: 2008 Certified

TAA Compliant



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

