

UNINTERRUPTIBLE POWER SYSTEM (UPS)

3000 VA, 2700 W, 120/240 VAC Auto Selectable input at 50 or 60 Hz input and 110/220 VAC switch selectable output at 50 or 60 Hz output, double conversion, rugged, high temperature, isolated, on-line UPS with hot swap battery drawer and optional EBP, and with power factor correction for Military applications.



Part # FA10159

Model # IHT3000RM-M-2.70Kw-DIACv-Isol-FC60-DOAC-24LiFeBHS-2U23.6

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)

| | |
|--------------------------|---|
| IP Part #: | FA10159 |
| IP Model #: | IHT3000RM-M-2.70Kw-DIACv-Isol-FC60-DOAC-24LiFeBHS-2U23.6 |
| Unit Description: | 3000 VA, 2700 W, 120/240 VAC Auto Selectable input at 50 or 60 Hz input and 110/220 VAC switch selectable output at 50 or 60 Hz output, double conversion, rugged, high temperature, isolated, on-line UPS with hot swap battery drawer and optional EBP, and with power factor correction for Military applications. |

SPECIFICATIONS

| | |
|------------------------------------|--|
| Power Rating: | 3000 VA, 2700 Watts |
| Input AC Voltage 1: | 120 or 240 VAC, (-25% +15%) |
| Input Frequency 1: | 50 or 60 Hz, (+/- 5 Hz) |
| Input Max Current: | 43.38 Amps |
| Output AC Voltage 1: | 110 or 220 VAC, (+/-3%) |
| Output Frequency 1: | 60 Hz, (+/-3 Hz), changer |
| Output Sync: | Sync to within +/- 1.5 Hz of input frequency |
| Enclosure Type: | 2U, rack mountable |
| Enclosure Dimensions: | English: 3.5 x 17 x 23.6 inch (Height x Width x Depth) Metric: 8.89 x 43.18 x 59.94 cm (Height x Width x Depth) |
| Enclosure Material and Finish: | Aluminum, powder coated charcoal gray |
| Enclosure Airflow: | Front to rear |
| Connector(s) AC Input 1: | 1 each NEMA L5-30P |
| -position: | On a 3' pig tail, rear |
| Connector(s) AC Output 1: | 1 each NEMA L5-30R |
| -position: | On a 3' pig tail, rear |
| Connector(s) EBP Group 1: | 1 each Locking Anderson |
| -position: | Panel mounted, rear |
| Battery Type 1: | 12.8V2.6Ah Lithium Iron Phosphate, 4-pack |
| Battery Quantity Total: | 24 |
| Battery Strings Quantity Total: | 3 |
| Battery Voltage per String: | 102.4 VDC |
| Battery Runtime 1: | Approximately 12 minutes at 2700 Watts |
| Battery Mounting: | Hot swap |
| Temperature Operating: | -20C to 50C (Celsius), -4F to 122F (Fahrenheit) |
| Humidity: | 5 to 95% non-condensing |
| PFC Feature: | Input power factor correction |
| Isolation: | Isolated |
| Application: | Shipboard |
| Fan Filters: | EMI |
| Auto Start: | Inverter output configured to start automatically, manual start available in settings |
| Cold Start: | Included |
| Overload Action: | Bypass at 111% |
| Conformal Coating: | Included |
| Communications - Remote: | SNMPv3.X |
| Switches and Breakers AC Input 1: | 2P40A, toggle |
| Switches and Breakers AC Output 1: | 1 each 1P25A, push to reset |
| Neutral Bonding: | Switch |
| Factory Default: | Unbonded |
| Controls Remote: | Undefined |
| Weight: | 80 lbs |
| Adapters - Input AC 1: | 6' IEC 60320 C20 to NEMA 5-20R adapter cable |
| Slide Rails: | TRUE |
| Monitoring and Control Apps: | ESX ESXi |

ISO 9001: 2008 Certified Facility

Military Standards



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

