

Uninterruptible Power System (UPS)

FA10434

All IntelliPower systems utilize circuit boards, chassis, components and construction techniques that are specifically designed for extreme environments—rugged, challenging thermal and/or shock and vibration applications. Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation, which provides ideal electrical output performance. Our standard build practices have enabled certified compliance to a number of performance standards for select models and product families. IntelliPower systems have proven performance in a wide range of key rugged military programs within the Army, Air Force, Navy and Marines. IntelliPower products are designed and manufactured in the USA, which means shorter lead times from design to shipping, as well as a level of personalized service unequaled in the marketplace.



Uninterruptible Power System (UPS)

Part #:	FA10434	Rev. 09172021
Model #:	IHT800-I-0.56Kw-120V-5060-120V-60-3LIHS-2U17	
Unit Description:	800VA, 560W, 120VAC 60Hz Input and 120VAC 60Hz Output, Frequency Converter, Non-Isolated, Power Factor Corrected, 2U Rack Unit, 3.5" High x 17" Wide x 17" Deep, Rugged, Double Conversion, to Provide Power Conditioning and Hot Swap Battery Hold-up for Industrial Applications	

INPUT RATINGS	
Input AC Voltage (AC Voltage, tolerance):	120 VAC, (-15% +15%)
Input DC Voltage (AC Voltage, tolerance):	N/A
Input Max Current (Amps):	50 or 60 Hz
Input Frequency (Hz, tolerance):	7.4 Amps @90VAC Input, 560W Output
PFC Feature:	Input Power Factor Correction
Breaker & Switch AC Input (type, location):	2P10A, Toggle Switch, Mounted Vertically, Magnetic Hydraulic Breaker, front panel
OUTPUT RATINGS	
Power Rating (VA, Watts):	800 VA, 560 Watts
Output AC Voltage (AC Voltage, tolerance):	120 VAC, (±3%)
Output DC Voltage (DC Voltage, tolerance):	N/A

(continued)

Output Frequency (Hz, follower/changer):	60 Hz +/- 1.5Hz, Changer
Output Sync Requirements:	N/A
Isolation (galvanic isolation/non-isolated):	Non-Isolated
Neutral Bonded to Ground (bonded/un-bonded/switch):	Un-bonded
Output AC Breaker & Switch (type, location):	1P10A, Push to Reset, Magnetic Hydraulic Breaker, rear panel
Output Overload – Shutdown or Bypass:	Alarm at 105%, Bypass at 115% of Full Load
MECHANICAL	
Enclosure Type & Size (type/rack unit, dimensions):	Rack Mountable 2U, 3.5"H x 17" W x 17" D
Enclosure Material & Finish (aluminum/steel finish):	Aluminum, Chem Film Coated with Charcoal Gray Powder Coat
Enclosure Airflow (front to rear/front to side/other):	Front-to-Rear
Nominal Weight +/- lbs.:	52 lbs. Maximum (Estimated)
Fan Filters (EMI/dust/comboination/grill):	Grill
Conformal Coated PCBAs (yes/no):	Yes
INTERFACE COMMUNICATIONS	
Serial Data Stream (SNMP v3/RS232, type):	SNMP, V3
Special (CIP, VMware ESX/ESXi/Other):	N/A
Discrete (Relay/Opto Description):	N/A
ADDITIONAL ELECTRICAL FEATURES AND CONTROLS/INTERFACE	
Auto Start (manual start/auto start):	Auto Start
Cold Start Switch (Yes/No):	No / (Optional)
CONNECTORS	
Connector(s) AC Input (type, location):	1 Each: IEC-320 C14 Inlet, Rear Panel
Connector(s) AC Output (type, location):	4 Each: NEMA 5-15R, Rear Panel
Connector(s) EBP/Charger (type, location):	None
BATTERIES	
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V 9.6 Ah, Lithium Iron Phosphate
Battery Total Quantity:	3 Batteries
Battery String Voltage:	36 VDC
Battery String (number of strings, quantity per string):	1 String, 3 Batteries per String
Battery Minimum Run Time (approx. run time at #watts):	30 Minutes at 560 Watts (80% Efficiency), 108 Minutes at 100 Watts (50% Efficiency)
Battery Mounting (hot swap/fixe):	Hot Swap Drawer
External Battery Module (EBM) PN:	N/A
EMI and ENVIRONMENTAL	
Application (shipboard/airborne/ground/all):	All
Temperature (Operating):	-10°C to +50°C
Humidity:	0-95%, Non-Condensing

Specifications subject to change without notice.